

CTF_5,5m/7m/9m

Manual lighting tower



Application fields



TECHNICAL DATA

Dimensions and weight

Min Dim. (cm) CTF 5,5m	26x28x190
Min Dim. (cm) CTF 7m	28x28x238
Min Dim. (cm) CTF 9m	28x28x250
Max Dim. (cm) CTF 5,5m	30x54x550
Max Dim. (cm) CTF 7m	35x106x700
Max Dim. (cm) CTF 9m	35x106x900
Weight (Kg)	67/85/93

Illuminated area

CTF 5,5m 4x500W - 625m²
CTF 7m 4x1000W - 1500m²
CTF 9m 4x1500W - 2000m²

Features

Rotation	360°
Floodlights	Halogen
Lamps	4x500W (CTF 5,5) 4x1000W (CTF 7) 4x1500W (CTF 9)
Lifting system	Manual
Optionals	NO

FEATURES

- Maximum height 5,5m/7m/9m
- Telescopic stainless steel mast
- Tower rotatable by hand through 360°
- Certified Wind stability up to 80 Km/h
Manual winch mast erection system with automatic brake, maximum load capacity 350/500 Kg with 133wires stainless steel
- 4 floodlights 500W halogen (**CTF 5,5m**)
- 4 floodlights 1000W halogen (**CTF 7m**)
- 4 floodlights 1500W halogen (**CTF 9m**)
- Lamps complete with bulbs
- Ideal for applications with containers and generators
- IP55protection