

CTF HAL/MH_5,3m

Manual lighting tower



Application fields



TECHNICAL DATA

Dimensions and weight

Min Dim. (cm) CTF 5,3m HAL	81x42x170
Min Dim. (cm) CTF 5,3m MH	120x42x170
Max Dim. (cm) CTF 5,3m HAL	81x42x530
Max Dim. (cm) CTF 5,3m MH	120x42x530
Weight (Kg)	121/132

Illuminated area

CTF 5,3m 4x500W HAL - 600m²
CTF 5,3m 4x400W MH - 1500m²

Features

Rotation	360°
Floodlights	Halogen Metal halide
Lamps	4x500W (CTF 5,3 HAL) 4x400W (CTF 5,3 MH)
Lifting system	Manual
Optionals	NO

FEATURES

- Maximum height 5,3m
- Telescopic galvanized mast
- Tower rotatable by hand through 360°
- Certified Wind stability up to 80 Km/h
- Manual winch mast erection system with automatic brake, maximum load capacity 350/500 Kg with 133wires stainless steel
- 4 floodlights 500W halogen (**HAL** version)
- 4 floodlights 400W metal halide (**MH** version)
- Lamps complete with bulbs
- Structure designed to be fixed onto the base of a trailer or a vehicle
- IP55 protection