



**DAUTEL**  
*FOLDER*

**DF 1000, DF 1500L**



## The flexible alternative

The flexible alternative for application conditions where a **DAUTEL LIFTER** is not needed at every loading position.



The combination of proven series parts of the **DAUTEL LIFTER** with new innovative components guarantees the legendary reliability. The version with 2 lifting and 2 double-acting tilting cylinders provides you the same ease of loading as the **DAUTEL LIFTER** because the platform tilt can be adjusted.

This allows highly flexible use of HGVs and centre-axle trailers up to a total weight of 15 t, ideal in transport operations and distribution transport, in car rental companies and in fresh produce logistics.

The hoist gear is slightly higher than the structure, depending on the system. A bridgeplate with impact buffer must be provided by the body manufacturer. In the case of refrigerated bodies, the floor structure of the body and the insulation value are consistently maintained. A special rear end section is not required. Depending on the system, trailer operation is only possible with a removable ball-type coupling on the underrun guard.



### Lightweight, easy handling

In the driving position the **DAUTEL FOLDER** is located under the HGV/body. Your benefit - free access to the rear of the vehicle means loading on ramps or container bridges is possible. The **DAUTEL FOLDER** is quickly and easily ready for use. The aluminium platform pack is set up hydraulically and the leading edge of the platform is easily unfolded by hand with the help of spring loading.



### Simplest assembly

The number plate holder and the fold-out roll are pre-assembled on the central section of the underrun guard, the tail light bracket is integrated in the underrun guard. Assembly can be carried out quickly due to the complete pre-assembly including suspended platform.

### Technical data

**Load capacity:** 1000 or 1500 kg for load centre 700 mm or 600 mm from the beginning/middle of the platform

**Platform size:** 1330 x 2200 mm, LxW

Technical data subject to change, illustrations non-binding. 09/2010



DAUTEL GmbH

Dieselstraße 33 · 74211 Leingarten · Germany  
Telephone +49 7131 407-0 · Fax +49 7131 407-107  
E-Mail [info@dautel.de](mailto:info@dautel.de) · Internet [www.dautel.de](http://www.dautel.de)